

**LISTING OF THE CLAIMS:**

A complete listing of the claims is provided below. This listing of the claims will replace all prior versions, and listing, of claims in the application.

1. (Currently Amended) Multilayer composite filter medium for serial filtration of an oil, the filter medium having ~~with~~ an onflow side and an outflow side with respect to a ~~medium~~ flow of the oil to be filtered, the filter medium comprising at least two filter layers, a first filter layer of the at least two filter layers having a particle retention size of 60 $\mu$ m and greater, a second filter layer of the at least two filter layers having a particle retention size of 10 to 60 $\mu$ m, wherein the at least two filter layers are essentially the same material and each layer of the at least two filter layers has a different respective filtering property and the at least two filter layers being welded to one another at defined regions, and at least one filter layer of the at least two filter layers being arranged on the onflow side and at least one filter layer of the at least two filter layers being arranged on the outflow side.

2. (Previously Presented) Multilayer composite filter medium according to claim 1, wherein at least one filter layer comprises a woven filter fabric and at least one filter layer comprises a nonwoven mat.

3. (Original) Multilayer composite filter medium according to claim 1, wherein thermoplastic filter media are used.

4. (Currently Amended) Multilayer composite filter medium according to claim 2, wherein the particle retention of nonwoven filter mat is ~~>60 $\mu$ m~~ >100 $\mu$ m.

5. (Currently Amended) Multilayer composite filter medium according to claim 2, wherein the particle retention of the woven filter fabric is ~~10 to 60 $\mu$ m~~ 25 to 45 $\mu$ m.

6. (Previously Presented) Multilayer composite filter medium according to claim 2, wherein the nonwoven filter mat and woven filter fabric comprise the same thermoplastic material.

7. (Previously Presented) Multilayer composite filter medium according to claim 1, wherein the regions make up 0.5 to 15% of a surface of the composite filter medium.

8. (Previously Presented) Multilayer composite filter medium according to claim 1, wherein the regions are arranged in the form of a grid on a surface of the filter medium.

9-12 (Cancelled)

13. (Original) Multilayer composite filter medium according to claim 1, wherein the filter medium is located in engine oil filters, transmission oil filters, fuel filters or air filters.

14. (Original) Multilayer composite filter medium according to claim 1, wherein the multilayer filter medium is located in a filter.

15. (Original) Multilayer composite filter medium according to claim 1, wherein the filter medium has a flat or pocket-shaped or pleated form.

16. (Currently Amended) A multilayer composite filter for serial filtration of a transmission fluid, the multilayer composite filter having ~~with~~ an onflow side and an outflow side with respect to a the fluid to be filtered, the composite filter comprising:

a first filter layer comprising a nonwoven mat, the first filter layer having a first edge, a first surface, and a second surface, wherein the first filter layer having a particle retention size of 60µm and greater;

a second filter layer comprising a woven filter fabric, the second filter layer having a particle retention size of 10 to 60µm, a second edge, a third surface, and a fourth surface, the second surface being disposed against the third surface to form an interface, the interface being

welded at a plurality of regions, wherein the first filter layer is arranged on the onflow side to filter coarser dirt particles relative to the second filter layer and the second filter layer being arranged on the outflow side to filter finer dirt particles relative to the first filter layer, and the first filter layer and the second filter layer are essentially the same media.

17. (Previously Presented) The composite filter according to claim 16, wherein the first filter layer and the second filter layer are comprised of a thermoplastic media.

18. (Cancelled) The composite filter according to claim 17, wherein the first filter layer and the second filter layer are comprised of essentially the same thermoplastic media.

19. (Previously Presented) The composite filter according to claim 17, wherein the first filter layer is comprised of a first thermoplastic media and the second filter layer is comprised of a second thermoplastic media, the first thermoplastic media and the second thermoplastic media having a similar melting point.

20. (Currently Amended) The composite filter according to claim 16, wherein the particle retention size of the first filter layer is ~~>60 $\mu$ m~~ >100 $\mu$ m.

21. (Currently Amended) The composite filter according to claim 16, wherein the particle retention size of the second filter layer is ~~10 to 60 $\mu$ m~~ 25 to 45 $\mu$ m.

22. (Previously Presented) The composite filter according to claim 16, wherein the regions make up 0.5 to 15% of the interface.

23. (Previously Presented) The composite filter according to claim 16, wherein the regions are arranged to form a grid within the interface.